

Product Data Sheet

Self Adhesive 80mic Semi-glossy White PVC Film

Description

Face material:

80mic semi-glossy white PVC Film

Adhesive:

Acrylic emulsion adhesive, excellent tack and broad application temperature range.

Backing:

135gsm white release paper

Typical value

Thickness (Face film)	80±8mic	(ISO 534)
Weight (Face film)	100±10g/m ²	(ISO 536)
Thickness (Adhesive)	21±3mic	(ISO 2808)
Thickness (Release paper)	140±15mic	(ISO 534)
Weight (Release paper)	135±10g/m ²	(ISO 536)
Peel Adhesion	≥7N/25mm	(FTM1 on stainless steel)
Shear Adhesion	>8h	(FTM8 on stainless steel)
Temperature ranges	Min.Appl.Temp: 10℃ Service Temp:-5 ~ 60℃	
Available Lengths&Widths	Custom sheet sizes available Roll width:100mm to 1070mm	

Application

This product is suitable for advertising and promotional campaigns, printed labels for interior and exterior decorations and works perfectly on smooth, thoroughly cleaned surfaces. With short to medium durability.

Printing Methods

Suitable for offset printing and also can be used for letterpress, screen printing. For best ink recommendations, please contact your ink supplier. Testing for suitability of media, printers and inks is always recommended prior to use.

Storage

Storage relative humidity: 50±5%
Storage temperature: 23±2℃
Storage time: 12 months

Attention

The application humidity range is 45% to 55%. Beyond this humidity range, customers are advised to use it after testing. Surfaces to be applied must be cleaned thoroughly of dust, grease or any contaminants. This information is based upon our knowledge and practical experience but does not constitute a warranty. All information is subject to change without prior notice.

RIGHTINT CO., LIMITED.

ADD: Room 616-617, Qibao International Building No.96, Lane 1333 XinLong Road, Minhang District, Shanghai

TEL: +86-021-36530656 Web: www.rightint.com