

## Product Data Sheet

### Self Adhesive Silver Glitter Film

#### Description

##### **Face material:**

100mic silver glitter film

##### **Adhesive:**

Acrylic water-borne adhesive featuring high clarity and high cohesion, and it has good removable performance on many material surfaces

##### **Backing:**

165gsm white release paper

#### Typical value

|                              |                                                            |                           |
|------------------------------|------------------------------------------------------------|---------------------------|
| Thickness<br>(Face film)     | 100±10mic                                                  | (ISO 534)                 |
| Weight<br>(Face film)        | 55±10g/m <sup>2</sup>                                      | (ISO 536)                 |
| Thickness<br>(Adhesive)      | 23±3mic                                                    | (ISO 2808)                |
| Thickness<br>(Release paper) | 167±12mic                                                  | (ISO 534)                 |
| Weight<br>(Release paper)    | 165±10g/m <sup>2</sup>                                     | (ISO 536)                 |
| Loop Tack                    | ≥6N/25mm                                                   | (FTM9 on stainless steel) |
| Peel Adhesion                | ≥5N/25mm                                                   | (FTM1 on stainless steel) |
| Shear Adhesion               | >2h                                                        | (FTM8 on stainless steel) |
| Release Force                | 13±8gf/25mm                                                | (FTM3)                    |
| Temperature ranges           | Min.Appl.Temp: 10℃<br>Service Temp:-20 ~ 80℃               |                           |
| Available<br>Lengths&Widths  | Custom sheet sizes available<br>Roll width:100mm to 1070mm |                           |

#### Application

Can be used in scrapbook layouts, handmade cards and invitations, labels, decals, lettering, striping, stickers, banners, bumpers, mugs, glass tumblers, containers, signs, wall decor, jewelry, paper crafts, kids' projects, collage art, kitchen containers, phone covers, laptop covers, windows and other decoration.

#### Storage

Storage relative humidity: 50±5%  
Storage temperature: 23±2℃  
Storage time: 12 months

#### Attention

The application humidity range is 45% to 55%. Beyond this humidity range, customers are advised to use it after testing. Surfaces to be applied must be cleaned thoroughly of dust, grease or any contaminants. This information is based upon our knowledge and practical experience but does not constitute a warranty. All information is subject to change without prior notice.

RIGHTINT CO., LIMITED.

ADD:Room 616-617, Qibao International Building No.96, Lane 1333 XinLong Road, Minhang District,  
Shanghai

TEL:+86-021-36530656 Web: [www.rightint.com](http://www.rightint.com)