

## Product Data Sheet

### Self Adhesive 80gsm Woodfree Paper

#### Description

**Face material:**

80gsm woodfree paper

**Adhesive:**

Acrylic emulsion adhesive, excellent tack and broad application temperature range.

**Liner:**

54gsm white glassine liner

#### Typical value

Thickness (Face paper)	97±5mic	(ISO 534)
Weight (Face paper)	80±5g/m <sup>2</sup>	(ISO 536)
Thickness (Adhesive)	21±3mic	(ISO 2808)
Weight (Adhesive)	20±3g/m <sup>2</sup>	(ISO 536)
Thickness (Release paper)	50±5mic	(ISO 534)
Weight (Release paper)	54±3g/m <sup>2</sup>	(ISO 536)
Loop Tack	≥10N/25mm (FTM9 on stainless steel)	
Peel Adhesion	≥6N/25mm PT (FTM1 on stainless steel)	
Shear Adhesion	>8h (FTM8 on stainless steel)	
Service temperature	Min. Appl. Temp: 5°C Service Temp: -20 ~ 80°C	
Available Lengths&Widths	Custom sheet sizes available Roll width: 100mm to 1080mm	

**Attention**

The application humidity range is 45% to 55%. Beyond this humidity range, customers are advised to use it after testing. Surfaces to be applied must be cleaned thoroughly of dust, grease or any contaminants. This information is based upon our knowledge and practical experience but does not constitute a warranty. All information is subject to change without prior notice.

#### Application

This product is suitable for a variety of promotional and industrial label applications. Typical applications include labeling systems for the cosmetics, pharmaceutical, and food industries.

#### Printing Methods

This product is suitable for flexo, letterpress, screen printing and offset, and can also be used for laser and inkjet printing, while for better printing, testing for the suitability of printers and inks is always recommended prior to use.

#### Storage

Storage relative humidity: 50±5%  
Storage temperature: 23±2°C  
Storage time: 12 months