

Product Data Sheet

Self Adhesive 90mic Fragile Paper

Description

Face material:

90mic fragile paper, easy for die cutting and stripping

Adhesive:

Acrylic adhesive, excellent tack and broad application temperature range.

Liner:

80gsm white glassine liner

Typical value

Thickness (Face film)	85±5mic	(ISO 534)
Weight (Face film)	160±5g/m ²	(ISO 536)
Thickness (Adhesive)	22±5mic	(ISO 2808)
Thickness (Release paper)	68±7mic	(ISO 534)
Weight (Release paper)	80±5g/m ²	(ISO 536)
Loop Tack	≥7N/25mm (FTM9 on stainless steel, face film reinforced)	
Peel Adhesion	≥6N/25mm (FTM1 on stainless steel, face film reinforced)	
Service temperature	Min.Appl.Temp: 5℃ Service Temp: -5 ~ 80℃	
Available Lengths&Widths	Custom sheet sizes available Roll width: 100mm to 1060mm	

Attention

The application humidity range is 45% to 55%. Beyond this humidity range, customers are advised to use it after testing. Surfaces to be applied must be cleaned thoroughly of dust, grease or any contaminants. This information is based upon our knowledge and practical experience but does not constitute a warranty. All information is subject to change without prior notice.

Application

Mobile phones, telephones, computer accessories, automobile electrical appliances, alcohol, medicine, food, cosmetics, performing arts tickets, and can also be used in shopping malls to prevent theft and tamper-proof.

Printing Methods

Suitable for flexo, letterpress, and screen printing. For best ink recommendations, please contact your ink supplier. Testing for suitability of media, printers and inks is always recommended prior to use.

Storage

Storage relative humidity: 50±5%
Storage temperature: 23±2℃
Storage time: 12 months

Shanghai RIGHTINT Self Adhesive New Material CO.,LTD

ADD: Room 616-617, Qibao International Building No.96, Lane 1333 XinLong Road, Minhang District, Shanghai

TEL:+86-021-36530656 Web: www.rightint.com